



DIRECT DRIVE TURNTABLES JBE

Superb examples of reliability, styling and precision engineering

With justifiable pride we bring you this superb range of direct-drive turntables. Quite possibly the best designed and attractive equipment available in the world today. With the exclusive off-deck control-box, and such a wide range of compatible tone-arms, your JBE System, aesthetically designed, meticulously engineered, and assembled with great care to your specific needs, dedicates itself to your lasting enjoyment.

JBE 3001

TYPE:

Manual player with direct-drive turntable

PLATTER:

Machined and balanced aluminium on black acrylic with centre-strobe disc,

or:

Solid platter with black rubber mat and rim-strobe

MOTOR:

24-slot 8-pole stator electronic control

Wow and flutter: specification 45507

Unweighted: better than 0.085%

Rumble: Din specification 44539

better than 43dB unweighted

better than 63dB weighted

DUST COVER:

Tinted acrylic

TONE ARM:

SME or Formula 4

SUSPENSION:

Microsorber feet

OPERATING:

Separate push-button control-box

SIZE:

17 1/8" x 13 1/8"





JBE 4001
As JBE 3001 but with black acrylic base.

JBE 5001
As JBE 4001 but with anodised aluminium on acrylic base.

JBE 6001
SIZE:
19½" x 14½"
Specifications as before, but with clear acrylic base and fitted with Ultimo tone-arm.

CHOICE OF THREE TONE ARMS



JBE 7001
SIZE:
19½" x 14½"
Specification as before, but with black acrylic base and fitted with Ultimo tone-arm.

JBE 8001
SIZE:
19½" x 14½"
Specification as before, but with anodised aluminium on acrylic base.

6001, 7001 and 8001 are designed specifically to take the DV505 tone arm.

CONTROL BOX

The JBE off deck control box incorporates on/off switch and 33 and 45 r.p.m. selection switches, plus fine speed controls to strobe.



The transformer is also situated in the control box thus minimising interference to tone arm and stylus head.

TONE ARMS

SME 3009 SERIES II

Non-detachable shell gives significant improvement to trackability and all-round definition, cleaner base, and low sensitivity to external shock and feedback.

FORMULA 4 PLS4/D

Properly damped for the lowest possible pivot-friction, this arm is also fully-adjustable for correct cueing, and is designed to obtain optimum performance with virtually any cartridge.

ONLIFE ULTIMO DV505

As its name implies this arm is the ultimate: the dual-pivot dynamic balance provides superb steadiness. The off-set angle is 21.5° . The lateral tracking at inner grooves is 0° ; at outer grooves the error is only 2.2° . Suitable cartridge weight including head shell is 9.35 grams. The lateral and vertical sensitivity is less than 50mg. The head shell is Standard EIA type.

SUMMITBEST LIMITED,
56-58 CLARENCE STREET,
KINGSTON-UPON-THAMES,
SURREY KT1 1NP, ENGLAND.
TELEPHONE: 01-549 0172/3.
'TELEX' messages addressed
to us are accepted by
Chamcon/London 888941
prefixed JOTCO



WORLDWIDE DISTRIBUTORS OF JB ELECTRONIC SYSTEMS AND EQUIPMENT